








STEADICAM® SYSTEMS CONFIGURATIONS

Camera Stabilizing Systems

DESCRIPTION	Ultra ² Cine	Ultra ² C	Clipper 324	Clipper 312	Archer ² SE	Archer ² S	Archer ²
Maximum Camera / Load Weight (Note: weights are approximate & conversions are rounded)	 48lbs/22kg	 48lbs/22kg	 35lbs/16kg	 35lbs/16kg	 30lbs/13.6kg	 30lbs/13.6kg	 26lbs/11.8kg
Dynamically Balanced Sled	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telescopic Post	4-Section	4-Section	3-Section	3-Section	2-Section	2-Section	2-Section
Post Length	28-72in / 71-183cm	28-72in / 71-183cm	26-49in / 66-124.5cm	26-49in / 66-124.5cm	23-35.5in / 58-90cm	23-35.5in / 58-90cm	23-35.5in / 58-90cm
Ultra Low Friction Gimbal	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Tilt Head	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Motorized Stage	Dual Axis Standard	Option	Option	Option	Dual Axis Standard	Single Axis Standard	Option
HD UltraBrite2, 8.4" Color TFT Monitor	Standard	Option	Option	Option	Option	Option	Option
HD 7" Color TFT Monitor	Option	Option	Option	Option	Option	Option	Option
TFT 7" Color Monitor 700nits AR coating	Option	Standard	Standard	Standard	Standard	Standard	Standard
Electronic Frameline Generator in Monitor	Standard Adjustable	Standard Adjustable	Option	Option	Standard Adjustable	Standard Adjustable	Standard Adjustable
Adjustable Monitor Bracket	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Adjustable Electronic Frameline Generator in Sled	Standard	Standard	Standard	Standard	N/A	N/A	N/A
Artificial Horizon	Standard	Option	Standard	Option	N/A	N/A	N/A
On-board Battery Status Display	Standard	Standard	N/A	N/A	N/A	N/A	N/A
Arm Type	G-70	G-70	G-50	G-50	G-50	G-50	G40
Boom Range	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm
Lightweight Ultra Vest	Standard	Standard	Option	Option	Option	Option	Option
Leather LX Vest	N/A	N/A	N/A	N/A	Standard	N/A	N/A
Lightweight LX Vest	N/A	N/A	Standard	Standard	N/A	Standard	Standard
Power Cube Battery Kit	Standard	Available	Standard	Available	Standard	Available	Available
Anton Bauer Battery Kit	N/A	Available	N/A	Available	Available	Available	Available
V-lock Battery Adapter	Standard	Option	Standard	Option	Option	Option	Option
AB Battery Adapter	Option	Option	Option	Option	Option	Option	Option
24V Power System	Standard	Standard	Standard	N/A	Standard	Standard	Standard
Low Mode Kit	Option	Option	Option	Option	Standard	Standard	Option
Balance / Operation Stand	Option	Option	Option	Option	Standard	Standard	Option
Hard Carrying Case	Standard	Standard	Standard	Standard	Standard	Standard	Standard

STANDARD = Item or feature is supplied with product as a default. OPTION = Item or feature can be incorporated into product order code. N/A = Item or feature is not available or not applicable to product. AVAILABLE = Item or feature can be ordered as separate line item.

The Tiffen Company • 90 Oser Avenue, Hauppauge, NY 11788 • Tel: 1-631-273-2500 • Fax: 1-631-273-2557 • e-mail: steadicam@tiffen.com • www.tiffen.com

Steadicam Manufacturing: 6933 San Fernando Road, Glendale, CA 91201 • Telephone 818-843-4600 x7913 • Fax: 818-843-8321 • Prices net FOB Los Angeles.

Robin Thwaites - International Director of Sales: Tiffen International Ltd., Unit 5, Avonbury Business Park, Howes Lane, Bicester, Oxfordshire, OX26 2UA, United Kingdom

Tel: +44 (0) 870 100 1220 • Fax: +44 (0) 1869 321 766 • e-mail: info@flysteadicam.com

All prices and specifications subject to change without notice. STEADICAM® is a registered trademark of The Tiffen Company. All other trademarks are the property of their respective owners. **VISIT US AT WWW.STEADICAM.COM**

The Steadicam Clipper 324 The Clipper 324 is an affordable 12/24 volt system for film and video applications.

- Low profile sled
- 700 nits SD NTSC/PAL monitor
- HD monitors optional
- Integral Frameline with artificial horizon
- 35lb/16kg net camera capacity
- 3-section post (26 - 49") (66-125cm)
- Lightweight LX vest
- Available motorized stage
- PowerCube battery included

The Steadicam Clipper 312 is an affordable system for standard high definition video products.

- Single/dual battery operation
- Available PowerCube battery
- Integral Frameline
- 700nit SD monitor
- Lightweight LX vest
- Artificial horizon (optional)
- 3-post (26 - 49") (66-125cm)
- G-50 Iso-Elastic Arm/LX Vest

Lease Options Available

STEADICAM TRAINING WORKSHOPS

Ask about our latest workshop schedule:

USA

Tel: 1-917-453-1219

www.thesteadicamworkshops.com

e-mail: steadicam@tiffen.com

UK (Tiffen International Ltd.)

Tel: +44 (0) 870 100 1220

www.flysteadicam.com

e-mail: info@flysteadicam.com



The Tiffen Company

90 Oser Avenue • Hauppauge, NY 11788

Tel: 631-273-2500 • Fax: 631-273-2557

Sales: 818-843-4600

email: steadicam@tiffen.com

www.tiffen.com • www.steadicam.com



The Tiffen Company

90 Oser Avenue • Hauppauge, NY 11788

Rev. 0909

BSTOREGAMI-P

The Steadicam Archer^{SE} comprises a unique, lightweight folding sled coupled to a lightweight open architecture stage and GEO series G-50 or G-40 arm. Post is extended for better balance options and the system is supplied with choice of battery mounting systems

- Lightweight carbon fiber sled with unique folding feature
- New "open architecture" stage assembly for greater rigidity and camera mounting stability
- Two section extending carbon fiber post
- Choice of GEO variable G-50 or GEO fixed G-40 multi-section compatible Iso-Elastic support arms
- Choice of battery systems
- Choice of monitor
- Lightweight LX vest

The Special Edition Archer^{SE} includes all the Archer's capability plus the following features:

- Leather Vest with socket block
- Steadicam Power Cube battery system - 2 x Power Cube / 1 x VL2 Charger
- Color 7" Monitor with Frameline-generator
- Tally system (Sensor included)
- Turtle base "C" Stand
- Hard Case for Arm/Vest & Sled
- Low Mode Kit
- 2 x Sand Bags / 1 x Tool pouch

The all new Steadicam Ultra² Series includes many of the revolutionary ideas introduced on the Ultra plus some outstanding new features. Key points include:

- New "open architecture" stage assembly for greater rigidity and camera mounting stability. Features motorized function and tilt head assembly
- New minimum profile sled
- Four section extending carbon fiber post assembly
- New stackable "PowerCube" high energy density battery system
- New Ultra: high precision gimbal
- New style locks and catches
- New G-70 GEO variable Iso-Elastic support arm
- HD UltraBRITE² monitor
- HD ready wiring
- Improved vest for greater user comfort and support without restricting mobility

The Steadicam Ultra² is a basic version of the award winning Ultra² system that allows the operator to customize it to their specific needs. Available features and options include:

- Motorized dual axis stage
- Choice of 8.4" HD UltraBrite monitor, 7" HD monitor or 7" Composite LCD monitor
- On-screen artificial horizon
- V-lock or Anton Bauer style battery mounts